



General Purpose Steel Fluted Returnable Reels for Wire & Cables - Class I

Type	REEL DIMENSIONS			Max OverAll Width	Arbor Hole Dia	Tire Size	I Beam	Loading Capacity	CROSS ARMS			Drum U.S.S Guage	Flange Head Sheet U.S.S Guage
	Flange	Traverse	Drum						U.S.S Guage	Long Inches	Short Inches		
RM	Inches	Inches	Inches	Inches	Inches	Inches	Inches	Lbs					
RM	42	24	24	33	3.25	2 x 5/16		1,956	8	5 x 2	4 x 2	12	16
RM	48	24	24	33	3.25	2 x 5/16		3,072	8	5 x 2	4 x 2	12	16
RM	54	32	32	41	3.25	2 x 5/16		4,464	8	5 x 2	4 x 2	12	16
RM	60	32	32	41	3.25	2 x 5/16		6,360	8	5 x 2	4 x 2	12	16
RM	66	32	36	41	3.25	2-1/2 x 1/2		7,680	8	6 x 2	5 x 2	12	16
RM	72	36	40	45	3.25	2-1/2 x 1/2		10,260	8	6 x 2	5 x 2	12	16
RM	72	36	48	45	3.25	2-1/2 x 1/2		7,872	8	6 x 2	5 x 2	12	16
RM	78	36	48	45	3.25	2-1/2 x 5/8	3	10,752	8	6 x 2	5 x 2	12	16
RM	84	36	42	45	5.25	7.5 lb /ft	3	13,608	8	7-7/8 x 2	6 x 2	10	16
RM	84	45	42	55	5.25	7.5 lb /ft	3	17,004	8	7-7/8 x 2	6 x 2	10	16
RM	84	45	56	55	5.25	7.5 lb /ft	3	11,196	8	7-7/8 x 2	6 x 2	10	16
RM	90	45	42	55	5.25	7.5 lb /ft	3	21,036	8	7-7/8 x 2	6 x 2	10	16
RM	90	45	56	55	5.25	7.5 lb /ft	3	15,216	8	7-7/8 x 2	6 x 2	10	16
RM	90	54	56	64	5.25	7.5 lb /ft	3	18,252	8	7-7/8 x 2	6 x 2	8	16
RM	96	60	42	71	5.25	7.5 lb /ft	3	26,000	8	7-7/8 x 3	6 x 3	8	14
RM	96	60	56	71	5.25	7.5 lb /ft	3	26,000	8	7-7/8 x 3	6 x 3	8	14
RM	108	74	56	85	5.25	7.5 lb /ft	3	30,000	8	7-7/8 x 3	6 x 3	8	14

Notes: RM Flat Bar Tire
 ** Generally used for aluminum wire and cable
 Alternate size 3 X 1/2in
 RMT - I beam tire

DO NOT USE OR REPRODUCE WITHOUT WRITTEN APPROVAL FROM STEEL CABLE REELS, LLC

General Purpose Steel Fluted Returnable Reels for Wire & Cables - Class II

Type	REEL DIMENSIONS			Max OverAll Width	Arbor Hole Dia	Tire Size	I Beam	Loading Capacity	CROSS ARMS			Drum U.S.S Guage	Flange Head Sheet U.S.S Guage
	Flange	Traverse	Drum						U.S.S Guage	Long Inches	Short Inches		
RM	Inches	Inches	Inches	Inches	Inches	Inches	Inches	Lbs					
RM	42	24	24	33	3.25	2 x 1/2		3,260	8	5 x 2	4 x 2	12	16
RM	48	24	24	33	3.25	2 x 1/2		5,120	8	5 x 2	4 x 2	12	16
RM	50	32	23	38	3.25	2 x 1/2		8,000	8	5 x 2	5 x 2	10	16
RM	54	32	32	41	3.25	2 x 1/2		7,440	8	5 x 2	4 x 2	12	16
RM	60	32	32	41	3.25	2 x 1/2		10,600	8	5 x 2	4 x 2	12	16
RM	66	32	36	41	3.25	2-1/2 x 1/2		12,800	8	6 x 2	5 x 2	10	16
RM	68	38	28	46	3.25	2-1/2 x 1/2		7,000	8	6 x 2	6 x 2	11	16
RM	72	36	40	45	3.25	2-1/2 x 5/8		17,100	8	6 x 2	5 x 2	10	16
RM	72	36	48	45	3.25	2-1/2 x 5/8		13,120	8	6 x 2	5 x 2	10	16
RM	78	36	48	45	3.25	2-1/2 x 3/4		17,920	8	6 x 2	5 x 2	10	14
RM	78	48	35	56	5.25	2-1/2 x 1/2	3	20,000	8	8 x 2	4 x 2	11	14
RMT	84	36	42	45	5.25	7.5 lb /ft	3	22,680	8	7-7/8 x 3	6 x 3	10	14
RMT	84	45	42	55	5.25	7.5 lb /ft	3	28,340	8	7-7/8 x 3	6 x 3	8	14
RMT	84	45	56	55	5.25	7.5 lb /ft	3	18,660	8	7-7/8 x 3	6 x 3	8	14
RMT	90	45	42	55	5.25	7.5 lb /ft	3	30,000	8	7-7/8 x 3	6 x 3	8	14
RMT	90	45	56	55	5.25	7.5 lb /ft	3	30,000	8	7-7/8 x 3	6 x 3	8	14
RMT	90	54	56	64	5.25	7.5 lb /ft	3	30,000	8	7-7/8 x 3	6 x 3	7	14
RMT	96	60	42	71	5.25	7.5 lb /ft	3	40,000	7	7-7/8 x 3	7-7/8 x 3	7	12
RMT	96	60	56	71	5.25	7.5 lb /ft	3	40,000	7	7-7/8 x 3	7-7/8 x 3	7	12
RMT	108	74	56	85	5.25	7.5 lb /ft	3	40,000	7	7-7/8 x 3	7-7/8 x 3	7	12

Notes: RM Flat Bar Tire
 ** Generally used for aluminum wire and cable
 Alternate size 3 X 1/2in
 RMT - I beam tire

DO NOT USE OR REPRODUCE WITHOUT WRITTEN APPROVAL FROM STEEL CABLE REELS, LLC